



PCX 60A

FORWARD PLATE COMPACTOR



FEATURES & BENEFITS

- 11kN high performance Vibrator for maximum compaction and excellent travel speeds.
- Sealed oil filled vibrator with top quality bearings for reli ability and durability.
- Ergonomic operator handle for precise manouverability, includes Pull-Back bar.
- Thickener Plate in rear of Baseplate for increased durability.
- Specially engineered Fabricated Baseplate designed to eradicate 'Track' marks on asphalt.
- Collapsable handle for easy storage & transportation.
- 3 mount HAV system for reduced HAV levels and improved usage time.
- Optional 'Easy-Fit' 12-litre Water Tank & 'Easy-Clean' Spray bar system.
- Durable metallic Water Control Tap for high flow rate.
- Low HAV handles that still allow precision control.
- Optional detachable 'Easy-Fit' Wheel Kit.
- Handle Latch for increased stability whilst operating the Wheel Kit.



OPTIONAL 'EASY-FIT' 12LTR WATER TANK



OPTIONAL INTEGRATED 'OUICK ENGAGE' WHEEL KIT



HANDLE LATCH FOR INCREASED STABILITY WHILST OPERATING THE WHEEL KIT

TECHNICAL SPECIFICATIONS

Model	PCX 60A	
Part No.	PCU02	
Plate Size (W x L)	(mm)	350 x 400
Width	(mm)	350
Length - Operation	(mm)	1010
Height - Operation	(mm)	1010
Length - Storage	(mm)	660
Height - Storage	(mm)	550
Engine Power	(Hp / kW)	3.3 / 2.4
*Weight	(kg)	68.5
Static Pressure	(kg/m^2)	565
Centrifugal Force	(kN)	11
Frequency	(Hz)	101
Max. Travel Speed	(m/min)	25
Max. Gradient	(°)	20
**Vibration level	(m/sec²)	4.9

Options

OPP/87/DIO Detachable Water Kit OPP/104/DIO Integrated Wheel Kit OPP/65/DIO Paving Pad

- * Weight does not include Water Kit or Wheel Kit.
- ** Vibration levels tested to BS5349 using EN 500-4



Sound Power Level



(dB Lwa)

105