



SE7500EC/TK1

7.5kVA Electro Fusion Spec Petrol Generator

GENERATOR SPECIFICATION	
Voltage	110v (55v/55v) CTE
Phase	1
Frequency	50Hz
Prime Power (PRP)	7.5kVA
Alternator	Meccalte S20W-110
Alternator Type	Brushless - Smooth Waveform
Fuel tank capacity	6.1 Litres
Autonomy 75% load	2.2 Hours
LWA	97
DBA @ 7M	72

ENGINE SPECIFICATION	
Engine	Honda GX390
Emissions certified	EU Stage V
Cylinders	Single
Distribution	O.H.V.
Aspiration	Naturally aspirated
Cooling	Air
Displacement	389 cm ³
Rpm	3000
Starting system	Recoil
Fuel	Unleaded 86 octane or higher



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	
810	630	730	84



CONTROL BOX

- Main MCB overload protection.
- 2 x 16A, 1 x 32A & 1 x 63A 110v BS4343 sockets.
- Reset circuit breaker overload socket protection.

STANDARD FEATURES

- 2 wheeled full wrap-around trolley frame.
- Oil alert/low oil shutdown.
- 3 Year engine warranty (Limited).
- Brushless smooth waveform alternator.

OPTIONS

- Electric start.
- LPG conversion.
- Long run tank (metal).
- AVR (Automatic Voltage Regulator).

POWER DEFINITION

Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.